

SAFETY DATA SHEET

DURABLE MAGNETIC HEAD CLEANING CARDS 5816-00

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air. Smoking is forbidden.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure limits

WEL (8 hr exposure limit): 400ppm (OES)

WEL (15 min exposure limit): 500ppm (OES)

Hazardous ingredients: PROPAN-2-OL

WEL (8 hr exposure limit): 999 mg/m³ WEL (15 min exposure limit): 1250 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Nitrile gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand. Face-shield.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Alcoholic

Solubility in water: Miscible

Boiling point/range°C: -82

Melting point/range°C: -88

Flammability limits %: lower: 2.50

SAFETY DATA SHEET

DURABLE MAGNETIC HEAD CLEANING CARDS 5816-00

upper: 12.70
Flash point°C: -11
Autoflammability°C: 398
Vapour pressure: 2.7
Relative density: >0-0.79

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Heat. Direct sunlight. Sources of ignition. Flames.
Materials to avoid: Strong oxidising agents. Strong acids.
Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: PROPAN-2-OL
IVN RAT LD50 1088 mg/kg
ORL MUS LD50 3600 mg/kg
ORL RAT LD50 5045 mg/kg
SCU MUS LDLO 6 gm/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.
Persistence and degradability: Biodegradable.
Bioaccumulative potential: No bioaccumulation potential.
Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1219
Packing group: II
Shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
Labelling: 3

ADR Class: 3
Classification code: F1
Hazard ID no: 33



SAFETY DATA SHEET

DURABLE MAGNETIC HEAD CLEANING CARDS 5816-00

IMDG / IMO

UN no: 1219 **Class:** 3
Packing group: II **EmS:** 3-06
Marine pollutant: NO **Labelling:** 3

IATA / ICAO

UN no: 1219 **Class:** 3
Packing group: II **Packing instructions:** 305(P&CA); 307(PAO)
Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Irritant.

Highly flammable.



Risk phrases: R11: Highly flammable.
R36: Irritating to eyes.
R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S7: Keep container tightly closed.
S16: Keep away from sources of ignition - No smoking.
S39: Wear eye / face protection.
S25: Avoid contact with eyes.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S51: Use only in well-ventilated areas.
S60: This material and its container must be disposed of as hazardous waste.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R11: Highly flammable.
R36: Irritating to eyes.
R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.