

SAFETY DATA SHEET

KEYBOARD & CASING WIPES

Page 1

Issued: 06/03/2007

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: KEYBOARD & CASING WIPES

Product code: 00-054

Company name: Durable UK Ltd

10 Nimrod Way

Wimborne

Dorset

BH21 7SH

Tel: 01202 897071

Fax: 01202 873381

Emergency tel: 01305 213770

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: PROPAN-2-OL 5-10%

EINECS: 200-661-7 CAS: 67-63-0

[F] R11; [Xi] R36; [-] R67

Contains: Benzalkonium chloride <1%

3. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Contaminated clothes should be laundered before reuse.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Consult a doctor. Remove to fresh air.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Water. Alcohol or polymer foam. Dry chemical powder. Water fog.

Exposure hazards: No significant hazard.

Protection of fire-fighters: Wear protective clothing to prevent contact with skin and eyes.

SAFETY DATA SHEET

KEYBOARD & CASING WIPES

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Contain the spillage using bunding.

Clean-up procedures: Wash the spillage site with large amounts of water.

7. HANDLING AND STORAGE

Handling requirements: Exercise normal standards of industrial hygiene.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: PROPAN-2-OL

WEL (8 hr exposure limit): 999 mg/m³ WEL (15 min exposure limit): 1250 mg/m³

Engineering measures: No significant hazard.

Respiratory protection: No significant hazard.

Hand protection: Exercise normal Industrial Hygiene

Eye protection: Ensure eye bath is to hand.

Skin protection: Avoid prolonged skin contact

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Pleasant

Solubility in water: Soluble

Relative density: 0.9-1.00

pH: 8-9

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Materials to avoid: Strong oxidising agents.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: PROPAN-2-OL

IVN RAT LD50 1088 mg/kg

ORL MUS LD50 3600 mg/kg

ORL RAT LD50 5045 mg/kg

SCU MUS LDLO 6 gm/kg

12. ECOLOGICAL INFORMATION

Mobility: Soluble in water.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

SAFETY DATA SHEET

KEYBOARD & CASING WIPES

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Disposal of packaging: Return to supplier.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

IMDG / IMO

IATA / ICAO

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Safety phrases: S2: Keep out of the reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S46: If swallowed, seek medical advice immediately and show this container or label.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R11: Highly flammable.

R36: Irritating to eyes.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.